



## Kaptec PRODUCT LINE CARD

### SCREW TERMINAL Plain and Stud Mounted

Series	Description	Temp	Life	Voltage Range
<b>KA</b>	General Purpose Compact	85°C	12,000 H	16V - 500V DC
→ <b>KB</b>	General Purpose Extended Sizes	85°C	12,000 H	350V - 450V DC
→ <b>KD</b>	Professional Long Life	85°C	20,000 H	350V - 550V DC
→ <b>KG</b>	Low E.S.R. high ripple capability	85°C	12,000 H	350 - 450V DC
→ <b>KI</b>	High Vibration capability	85°C	12,000 H	16V - 500V DC
→ <b>KE</b>	Imperial sizes high CV	85°C	2,000 H	400 - 450V DC
<b>KC</b>	Professional High temperature	105°C	5,000 H	16V - 450V DC
→ <b>KH</b>	Low E.S.R. high ripple capability	105°C	5,000 H	350 - 450V DC
→ <b>KJ</b>	High Vibration capability	105°C	5,000 H	16 - 450V DC
<b>KF</b>	Strobe - Charge / Discharge	70°C		400 - 500V DC
<b>KK</b>	Professional Audio Applications	85°C	12,000 H	63 - 100V Dc

### SNAP-IN 2 Pin and 4 Pin

Series	Description	Temp	Life	Voltage Range
<b>KL</b>	General Purpose Compact	85°C	5,000 H	16 - 500V DC
→ <b>KM</b>	General Purpose Large Sizes	85°C	5,000 H	400 - 450V DC
→ <b>KR</b>	Low E.S.R. high ripple capability	85°C	12,000 H	400 - 450V DC
<b>KN</b>	Professional High temperature	105°C	5,000 H	16 - 450V DC
→ <b>KP</b>	Professional Extended Sizes	105°C	5,000 H	400 - 450V DC
→ <b>KS</b>	Low E.S.R. high ripple capability	105°C	8,000 H	400 - 450V DC